

## PERFORMANCE DATA SHEET

CLAROSWISS® N-series water filters  
500 N, 1000 N, 1500 N, 2000 N

### Substance reduction

The Water Filter models listed above are certified under AS 3497 and relevant NSF/ANSI 42 for reduction of chlorine. The performance of these products has been tested and verified on a representative model (ClaroSwiss 500 N) and substantiated as the test data summarized below indicates.

### Tested item: ClaroSwiss 500 N

Substance	<sup>a</sup> NHMRC ADWG or <sup>b</sup> USEPA SDWA MCL	Average Influent Concentration	NSF/ANSI influent challenge concentration	% reduction reqt/ max permissible product water concentration	Maximum Effluent Concentration	Minimum Percent Removal	Average Effluent Concentration	Average Percent Removal	Average Flow rate liters per minute
Chlorine	0.6 mg/L	2.0 mg/L	2.0 mg/L	50 %	0.3 mg/L	85.7 %	0.13 mg/L	93.3 %	1.965

### Lab Testing Conditions:

Flow Rate:	2 lpm (0.5 gpm)	Refer to your Owner's Guide for more specific product and warranty information and to avoid contamination from improper handling and installation. Performance will vary based on local water conditions. The substance reduced by this product is not necessarily in your water.
Pressure:	413.7 kPa (60 psi)	
pH:	7.5 ± 0.5	
Temp:	20 ± 3° C (68 ± 5° F)	

mg/L – milligrams per litre (1mg/L = 1 part per million)

<sup>a</sup> National Health and Medical Research Council Australian Drinking Water Guidelines

<sup>b</sup> United States Environmental Protection Agency (USEPA) Safe Drinking Water ACT

These cartridges meet the domestic water treatment appliance Standard AS 3497 and NSF/ANSI 42 for the following water treatment processes:

Category	Treatment type	Function	Pass
I	Microbiological Status: Bacteriostatic	Will stop bacteria increasing, but will not remove them unless II(a) is passed	N/A
II / II(a)	Microbiological Treatment: Bacteria Removal	Will remove or inactivate bacteria	N/A
II(b)	Virus removal	Will remove or inactivate viruses	N/A
II(c)	Protozoa removal	Will remove or inactivate Cryptosporidium and Giardia. Will not remove or inactivate bacteria and viruses unless Class II(a) and II(b) are passed	N/A
III	Turbidity and particulate removal	Reduces cloudiness	N/A
IV	Taste and Odour reduction	Reduces tastes and odours	PASS
V	Chemical treatment	Decreases Chlorine	PASS

#### Guidelines for use

Minimum and Maximum operating temperature	4° - 30° C (39° F - 86° F)
Nominal flow rate	2L/min
Minimum and Maximum inlet water pressure	2 - 8 bar (200 - 800 kPa)
Replacement of filter cartridge	Recommendation for cartridge replacement: 6 month, latest 12 month after installation or earlier, if capacity is exhausted

This system has to be installed according to local plumbing codes on the cold-water line

ACLARIS Water Filter cartridges are not covered by standard ACLARIS warranty as filter life may vary according to water quality and rate of use.

**CAUTION - DO NOT USE WITH WATER THAT IS MICROBIOLOGICAL UNSAFE OR WITH WATER OF UNKNOWN QUALITY WITHOUT ADEQUATE DISINFECTION BEFORE OR AFTER THE SYSTEM. SYSTEMS CERTIFIED FOR CYST REDUCTION MAY BE USED ON DISINFECTED WATER THAT MAY CONTAIN FILTERABLE CYSTS.**

#### Manufactured by:

##### Switzerland

ACLARIS GmbH  
Lindau, Zweigniederlassung Rebstein  
Balgacherstrasse 20, CH-9445 Rebstein  
+41 71 775 92 40, info@aclaris.com

[aclaris.com](http://aclaris.com)